Solarthon




51.2 V 100Ah Battery Pack

Energy Storage System

- ▶ Safe lithium iron phosphate battery.
- > Small and ultra-light modules.
- ▶ Each battery pack is equipped with an intelligent battery management system to effectively manage the modules.
- Compared with traditional modules, it can meet the capacity storage and greatly improve the cycle life.

PRODUCT DETAILS






BATTERY DETAIL

- Iron Phosphate Safety Battery
- Each battery pack is equipped with intelligent BMS to manage modules effectively
- Compared with traditional modules, it can meet the capacity storage and greatly improve the cycle life

- LiFePO4 battery, safe and longer life
- 51.2 kWh energy capacity, parallel up to 54 kWh
- Free cooling with optional cooling/fan configuration
- Wide temperature range, -20~50°C

- Small size and light weight
- High power input and available energy ratio
- Modular design, expandable system
- Safest battery and perfect compatibility
- Natural cooling, easy installation
- Certification available



BATTERY CABINET




PRODUCT SPECIFICATION

Model	STFBC001
Dimension(WDH)	600x600x882.5mm
Partition	4
Material	Ion steel
Proctect Level	IP20
Max.Power	20Kwh
Warranty	3 years

- Standard 3U chassis size.
- Adopt high-quality, stable, long-life aluminum shell LiFePO4 battery.
- With charging current limiting function, it is safer when connected in parallel.
- The design adopts dual-port output, which is more convenient for parallel connection.
- Precise LED power display and status display.

BATTERY CABINET LINE DRAWING



DIFFERENT ANGLES OF BATTERY CABINETS



PRODUCT SPECIFICATION

Model	STF512100
Nominal Voltage	51.2V
Capacity	100Ah
Nominal Energy	5.12kWh
Discharge Voltage	45~54V
Charge Voltage	51.5V~54V
Cont. Charge Current	30A
Cont. Discharge Current	30A
Max. Discharge Current	50A
Operating temperature	0° C ~ 45° C (Charge) /- 20° C ~ 45° C (Discharge)
Scalability	Up to 5 units
DOD	90%
Communication	CAN/RS485
Cycle Life	>6000
IP Grade	IP20
Installation	Cabinet
Dimension	440*530*132mm
Weight	45kg
Warranty	3 Years



